

Product information

Features

- * Adjustable seat height, back height and seat depth.
- * Automatic adjustment of the swing resistance, can be easily fine-tuned.
- * Adjustable seat inclination in two positions (normal and angled forward).
- * Lockable back angle in several positions.
- * Seat height 400-520 mm as standard (soft seat 420-540 mm).
- * Black swivel base with unbraked wheels for hard floors as standard.



Options

- * Upholstered back in three different heights; 40 (height 48 cm), 50 (height 59 cm) and 60 (height 67 cm).
- * Mesh back 50 (height 59 cm).
- * Upholstered seat in three versions, small, medium and soft.
- * 40 backs have a small seat as standard, 50 backs have a soft seat, 60 backs have a medium seat.
- * Adjustable armrests: 2D in width and height, 4D in width, height, angle and depth, 4D plus in width, height, depth and 360 degree angle.
- * Adjustable headrest in height and depth (can be retrofitted).
- * Foot crosses are available in gray, polished, black nylon and black lacquered aluminum.
- * Interval braked wheels for hard floors (locks without load), braked wheels for hard floors (locks under load), unbraked wheels for soft floors.
- * Lumbar support for 50 and 60 heights upholstered back

Quality

- * Approved according to EN 1335: 1-2-3 type B, EN 1335-2, EN 1335-3.
- * Savo provides a 10-year warranty against manufacturing defects during normal 9-hour sitting.
- * Tested and approved in additional tests for more severe use (ie 24/7) according to ISO 7173:1989 chapter 7.1 – 7.6 och 7.11 – 7.13. Test level 5.
- * For 24/7 use of the chair, 2 years warranty applies
- * Warranties do not apply to wear and tear. Warranties apply to materials, not work
- * Möbelfakta-certified variants are available.

Standard dimensions



Modell	Seat height standard lift	Seat dimensions Width x Depth	Back dimensions Width x Height	Seat depth adjustment
Mesh	420 - 540	485 - 460	420 - 590	400 - 480
40	400 - 520	455 - 450	400 - 480	390 - 470
50	420 - 540	485 - 460	420 - 590	405 - 485
60	400 - 520	475 - 490	420 - 670	410 - 490